



one world_one brand_one level_

LevelOne Fast Ethernet Switch

LevelOne 10/100Mbps Fast Ethernet Switch



TECHNICAL DATA

Standard Conformance

- IEEE802.3 10Base-T Ethernet
- IEEE802.3u 100Base-TX Fast Ethernet
- IEEE802.3x Flow Control and Back-pressure
- ANSI/IEEE 802.3 Auto-negotiation

Physical Ports

- 5/8 10/100Mbps STP RJ45 auto-negotiation ports
- Auto MDI/MDIX crossover for all ports

Forwarding and Filtering Rate

- 14,880 pps per Ethernet port
- 148,800 pps per Fast Ethernet port

Network Cables

- 10Base-TX: 2-pair UTP/STP Cat. 3, 4, 5 cable
EIA/TIA-568 100-ohm (100m)
- 100Base-TX: 2-pair UTP/STP Cat. 5 cable
EIA/TIA-568 100-ohm (100m)

LED Indicators

- Per Port: Link/Activity (100M green, 10M yellow)
- Per Unit: Power

Power Input

- DC 7.5V/0.8~1A external power supply

Physical Characteristics

- Storage Temperature: -40°C to 70°C
- Operational Temperature: 0°C to 50°C
- Storage Humidity: 5% to 90% RH
- Operational Humidity: 10% to 50% RH

Dimensions

- 127 mm x 70 mm x 28 mm (L x W x H)
- Weight: 0.74kg

Ordering Information

- FSW-0508TX 5 Port 10/100Mbps Fast Ethernet Switch
- FSW-0808TX 8 Port 10/100Mbps Fast Ethernet Switch